



For Rotary Electric Actuators

E Series

This specification covers the design of rotary electric actuators used in plant-wide valve automation applications.

- Electric rotary actuator shall be reversible type with capacitor run motor and with permanently lubricated hardened steel gearing
- Housing/enclosure shall be die cast aluminum with a thermally bonded polyester powder coating and stainless steel trim to meet NEMA 4 and 4X for corrosion resistance.
- Each actuator shall be available with a manual override, visual position indicator and ISO-5211 standard mounting arrangement.
- Actuator shall be fitted with a minimum of two SPDT limit switches that are used to shut off the motor at specific points in rotation and that may also be used for light indication.
- Actuator housing shall meet NEMA4 and be available with optional NEMA7 enclosure for hazardous area applications.
- All motors will come standard with an integral thermal overload protection.
- Output/drive shaft and fasteners shall be stainless steel.
- Conduit entry shall be 1/2" NPT except Models E-2000 and E-3840 which have 3/4" NPT.
- Electric rotary actuator shall be SVF Series "E" or equal.



What do you need today?™

HIGH PURITY
CleanFLOW
www.CleanFLOW.net

PRO-SPEC
PROCESS SPECIFIC
WWW.PRO-SPEC.NET

QUALITY FLOWS
THROUGH US

Specifications subject to change. Visit www.SVF.net for the latest updates on this Specification Sheet. All Data posted on our website supersede all prior publications • [Document #PSG-ESeries-12_2010] • E Series Specifications - 12/27/2010

www.SVF.net

SVF Flow Controls, Inc. • 13560 Larwin Circle • Santa Fe Springs, CA 90670 • Tel: 1.800.783.7836 • FAX: 562.802.3114
Sales@SVF.net • Visit our website: www.SVF.net • © SVF Flow Controls, Inc. • Specifications subject to change without notice